

Performa Cv Control Valves

273 and 278 Configurations



Pentair Water® offers a full range of Autotrol® Control Valves to meet a wide range of water conditioning applications.

Logix™ Series

742 Time Clock

- Simple, economic electronic time clock (chronometric)
- 7- or 99-day regeneration
 - 12-voit operation
 - Filter or conditioner setting in one control
- Fully programmable cycle times
- Salt : Fine and in repound increments
 - Operates 255, 263, 268 273, 278, and Magnum IT with one controller

Marine Marine and a contract


- Simple, economic electronic demand (volumetric)
- Calendar override
- 12-volt operation
- 28-day variable reserve
- Automatic capacity calculations
- Fully programmable cycle times
- Salt setting in 1-pound increments
- Operates 255, 263, 268, 273, 278, and Magnum IT with one controller.

Annual Control of the Control of the

Same features as the 762, plus:

- Multi-tank applications (twin a ternating, multitask appelled)
- Control lockou
- .







Dimensions


Valve Connections


Tank Thread 2-1/2-inches - 8, male

Inlet/Outlet Threads 1-3/4-inches - 12 UNC-2A male

Drain Line 3/4-inch NPT, male Brine Line 3/8-inch NPT, male Distributor Tube Diameter 1.050 inches (27 mm)

Distributor Tube Length $1/2 \pm 1/2$ -inches (13 ± 13 mm) above top of tank





Injector* Performance

